STANDARD Pump, Inc.













Sanitary Drum Transfer Pumps SP-8600 & SP-8700

SP-8600 / SP-8700 Series





Hygienic drum pump solutions for transferring sanitary products.

Standard Pump is the global leader in Hygienic Drum Pump solutions and offers a broad range of pumps to meet the stringent safety requirements of the sanitary process industry. Standard Pumps' SP-8600 & SP-8700 Series sanitary centrifugal pumps offer the ideal solution for transferring juices, concentrates, beer, wine, and cosmetic fragrances from barrels, kettles and Tote® tanks. The SP-8600 & SP-8700 Series pumps incorporate a proven hygienic design and FDA Compliant materials of construction (CFR 21.177) insuring a safe, robust and efficient sanitary solution.



Features

- · FDA Compliant Materials of Construction
- · Hygienic Design
- · Easy to Clean
- · Tri-clamp® Fittings
- · Light Weight & Portable
- · Variable Speed Electric & Air Motors
- · Runs Dry

Common Applications

- · Juices
- · Concentrates
- · Personal Care Products
- · Pharmaceuticals
- · Beer
- ·Wine
- · Cosmetic Fragrances

Technical Specifications

Model Number: SP-8600-39, SP-8600-47

SP-8700-39, SP-8700-47

Immersion Length: 39" (1000 mm) Drums

47" (1200 mm) Tote® Tanks and Kettles

Wetted Components: SS316L, PTFE & Buna

Motor Drive: SP-280P, SP-ENC, SP-A1, SP-A2, SP-400 Series

Discharge Size: 1.5" (38 mm) Tri-clamp® Connection


Maximum Viscosity:1,000 cps (mPAS)*Maximum Discharge Pressure:43 psi (2,9 bar)Maximum Flow Rate:35 GPM (132 LPM)

Pump Shipping Weight:


PN: SP-8600-39, SP-8700-39
PN: SP-8600-47, SP-8700-47
12 lbs (5,5 kg)
14 lbs (6,4 kg)
Maximum Temperature: 175° F (80° C)

Flow Curves

High Volume Pumps (SP-8600 Series):



High Pressure Pumps (SP-8700 Series):



Flow Rate (Based On Water)


5 SP-280P, SP-ENC | **6** SP-420EX,S SP-A2 | **7** SP-A1 | **8** SP-410EX

Note: Pump is constructed with FDA compliant materials; however, the pump does not have FDA certification.

^{*}Pump is intended for intermittent use when operating at maximum viscosity.

SP-8600 / SP-8700 Series

Pump Component Features Optional-Hose Barb Optional-High Performance Spout Stainless bearings Connection PTFE Guide Sleeve Tri-clamp® stabilizes the drive shaft Discharge Fitting Sealless design allows operator to apply back pressure or run dry ACME Stub threads for quick replacement of spare parts and Self priming disassembly for fast cleaning SS316L impeller and sanitization



Motor Drives SP-280P SP-ENC (EXP) SP-A1 SP-A2 (air)



PURE PUMP Series










Additional Sanitary Products Available:



Air Operated Diaphragm Pumps



3A Drum Pumps



FDA Compliant Drum Pumps



Batch Control Systems

Distributed By:

STANDARD Pump, Inc.

World Headquarters 1540 University Dr. Auburn, Georgia 30011 USA

1.866.558.8611 Tel 770.307.1003 Fax 770.307.1009 www.standardpump.com

STANDARD PUMP Europe

Vølundsvej 12 3400 Hillerød Denmark

Tel +45 7023 2100 Fax +45 7023 5655 www.standard-europe.eu



For more information scan this QR code with your smartphone.